

# LOCTITE®

3.5 OZ.

LOCTITE®

2.0 OZ.

COMPETITION

Comparison of pouch size of Loctite® 5<sup>th</sup> Wheel Grease vs. the Competition

**KRAYDEN, INC.**  
AUTHORIZED DISTRIBUTOR  
1-800-448-0406

# SIZE DOES MATTER

With **NEW Loctite® 5<sup>th</sup> Wheel Grease**,  
you get **75% more product!**

- Requires no tools, creates no mess
- Packaging disintegrates, leaving no waste
- Designed to lubricate 5<sup>th</sup> wheel top plates of trailer
- Graphite and molybdenum disulfide lubricant
- Effective at extreme temperatures and environmental conditions
- Full 3.5 oz in every pouch



## ORDERING INFORMATION

ITEM NUMBER	DESCRIPTION	SIZE	CASE QUANTITY	WEIGHT
<b>1291112</b>	Loctite® 5 <sup>th</sup> Wheel Grease	3.5 oz. (99 g) Pouch	1 Display Box containing 24 Pouches	6 lbs. (2.2 kg)

## TECHNICAL INFORMATION

COLOR	BASE OIL	NLGI GRADE	WATER RESISTANCE	TEMPERATURE RANGE	FOUR BALL WEAR TEST
Black	Soap Grease 30% Solids	1.0	Yes	-20°F (-29°C) to 250°F (121°C)	0.80 mm <sup>2</sup>

Henkel



Call today at **1-800-LOCTITE (562-8483)**  
or visit us on the web at  
**www.henkelna.com/truckgrease**  
for more information

**KRAYDEN, INC.**

AUTHORIZED DISTRIBUTOR  
1-800-448-0406



**LOCTITE®**

RETRACT TUBE

LANDING GEAR

GEARBOX

KING PIN

# ONE PRODUCT

## FOR ALL TRAILER AND JACK STAND APPLICATIONS

### Introducing NEW Loctite® Trailer Jack Stand Grease

- Use to lubricate landing gear housing, retract tube and gearbox
- Specially formulated for lubricating king pins, bushings, slide ways and landing gear screws/nuts
- Multipurpose/high-performance grease for sliding applications
- Corrosion- and water-resistant
- Synergistic additive system for enhanced film strength
- Extreme pressure and anti-wear protection



#### ORDERING INFORMATION

ITEM NUMBER	DESCRIPTION	SIZE	CASE QUANTITY	WEIGHT
<b>1289249</b>	Loctite® Trailer Jack Stand Grease	400 g (14 oz.) Cartridge	12	12 lbs. (5.4 kg)

#### TECHNICAL INFORMATION

COLOR	BASE OIL	NLGI GRADE	WATER RESISTANCE	TEMPERATURE RANGE	FOUR BALL WEAR TEST
Black	Lithium 12-Hydroxy	1.5	Yes	-10°F (-23°C) to 392°F (200°C)	0.55 mm <sup>2</sup>



Henkel Corporation  
Engineering Adhesives  
One Henkel Way  
Rocky Hill, CT 06067  
Tel: 860-571-5100 • Fax: 860-571-5465  
[www.henkelna.com](http://www.henkelna.com)

**Call today at 1-800-LOCTITE (562-8483)**  
or visit us on the web at  
**[www.henkelna.com/truckgrease](http://www.henkelna.com/truckgrease)**  
for more information

® and ® designate trademarks of Henkel Corporation or its affiliates. ® = registered in the U.S. Patent and Trademark Office. © Henkel Corporation, 2009. All rights reserved. 6006/LT-5656 (08/09)